

CHROMA™

Global Flooring Solutions

Maintenance Instruction for Dennebos by Chroma – Please read and action accordingly.

All Dennebos by Chroma engineered floor boards are finished with industrial Dennebos Hard Wax Oil, composed of high-quality natural ingredients.

Immediately after the floor has been installed, and before occupation or installation of any furniture items, wood boards should be treated once with Dennebos Maintenance Oil transparent or white. (fine sawn/tate floor boards are treated with Hard Wax Oil instead of maintenance oil)

INSTRUCTIONS FOR DENNEBOS MAINTENANCE OIL

Dennebos Maintenance Oil (transparent/white) is best applied evenly and lengthwise along the wood grain with a short-haired mohair roller or a non-pilling cloth.

Dennebos Maintenance Oil (transparent/white) may, if so desired, be polished immediately after application. This is done preferably by using a buffing machine with a white pad underneath.

After application, the oil needs approximately 12 - 14 hours to dry.

Depending on the intensity/load of the floor, daily maintenance by vacuum with a brush or by wiping the floor with a wiper (micro fibre) will do.

Also, you can clean your floor weekly with Dennebos Parquet Cleaner. Dennebos Parquet Cleaner is so composed that, when used according to the instructions, it does not corrode the oil finish and it does not leave any soap residue.

INSTRUCTIONS DENNEBOS PARQUET CLEANER

Only add one cap of Dennebos Parquet Cleaner to a bucket of warm water (app. 10 litres). Then mop the floor with a slightly moist cloth, make sure no small pools of water are left.

Stains or shoe-markings may be removed by applying Dennebos Parquet Cleaner undiluted to a non-pilling cloth and wipe out the stain lengthwise along the wood grain. Wipe immediately after treatment with lukewarm water.

Should the floor become less beautiful when cleaning only with Dennebos Parquet Cleaner and it starts to show wear spots, the floor should be treated with Dennebos Maintenance Oil white or transparent, to saturate the wood

CHROMA™

Global Flooring Solutions

Please note:

Oiled wood floors are most vulnerable in the first 14 days after installation because the oil has not yet fully hardened. For a complete and proper hardening, it is important not to walk or install furniture to protect your floor as much as possible. Please be extremely careful only to use Dennebos approved products and limit water and moist.

Dennebos Maintenance Oil white should only be used on floors where a white oil treatment has been applied at the factory.

After installing the white oil, please take care of proper ventilation during the drying time.

The temperature of the room should always be kept between 15- 22° Celsius.

Relative humidity should be between 40% and 65 %.

Do not use any other cleaning agents, these will permanently damage your floor, or leave a permanent film that cannot be removed without sanding, and or it may even affect the hard wax oil.

MAINTENANCE TIPS

Wait at least 48 hours before placing any furniture on the floor.

Always protect your new floor with furniture covers or small pieces of felt or carpet underneath your furniture. This prevents scratches and damage when furniture is moved.

Please do not cover the floor in the first two weeks, as hard wax oil needs to dry completely and oxides. This process can take up to six months.

In the first two weeks the floor should only be vacuumed or cleaned with a dust cloth (like Swifter for example), do not wipe with water.

Wait at least 3-6 months before applying carpets or rugs in order to prevent shade variations.

Provide proper barrier matting, both inside and out your main door. This will reduce dirt from entering the building and damaging the floor. Also, this will keep your flooring looking better between periodic maintenance, and it will avoid unwanted scratches and damage.

CHROMA™

Global Flooring Solutions

MAINTENANCE ADVICE

Dry clean your floor daily, vacuum with a brush, or even better, wipe it with a dust cloth (for example with Swifter or micro fibre cloths). A floor wiper takes up more sand and dirt from the floor than a wet mop. If you do this daily, you'll find that your floor shows fewer wear spots.

If necessary, you may wipe the floor with a slightly moist cloth with warm/hot water, mixed with Dennebos Parquet Cleaner. Dennebos Parquet Cleaner cleans very thoroughly and at the same time feeds the wood, preventing the oil to wear away.

When you drop or spill anything, it should be cleaned immediately with a slightly moist cloth with lukewarm water, which may be mixed with Dennebos Parquet Cleaner.

Dry properly.

Stains or shoe markings may be removed by applying Dennebos Parquet Cleaner undiluted to a non-pilling cloth and then wiping the stain lengthwise along the grain. Wipe off with lukewarm water immediately after treatment.

Should the floor appear dull when only cleaning with Dennebos Parquet Cleaner and it starts to show wear spots, the floor should be treated with Dennebos Maintenance Oil white or transparent, to re-saturate the wood.