

OBJECT CARPET

Typical characteristics EN 1307

Name of article:	Black Art Lava
Method of production ISO 2424:	woven
Width ISO 3018:	ca. 190 cm
Surface structure ISO 2424:	Loop
Colourways ISO 2424:	patterned Rapport/pattern repeat L 52 cm x B 47,5 cm
Pile material:	100% Polyamid - Antron® Legacy
Primary backing ISO 2424:	synthetisch / synthetic / synthétique
Secondary backing ISO 2424:	Appretur
Overall weight ISO 8543:	ca. 1.600 g/m ²
Overall thickness ISO 1765:	ca. 4,0 mm
Mass of effective pile ISO 8543:	ca. 400 g/m ²
Pile service weight:	ca. 500 g/m ²
Effective pile thickness ISO 1766:	ca. 3,0 mm
Pile density ISO 8543:	
Stitch rate ISO 1763:	112.000 / m ²

Application

Wearability:	33
Comfort class:	LC 1

Physical features as to the building

Electrostatic loading:	< 2 KV														
Surface resistivity:	10 ⁹ Ω														
Sound absorption:	+18 dB														
Acoustical absorption α_w	0.15														
Sound absorption α_s	<table><thead><tr><th>Hz</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr></thead><tbody><tr><td>α_s</td><td>0,01</td><td>0,01</td><td>0,03</td><td>0,14</td><td>0,23</td><td>0,11</td></tr></tbody></table>	Hz	125	250	500	1000	2000	4000	α_s	0,01	0,01	0,03	0,14	0,23	0,11
Hz	125	250	500	1000	2000	4000									
α_s	0,01	0,01	0,03	0,14	0,23	0,11									
Transparency to heat:	ca. 0,06 K*m ² /W														
Flammability EN 13 501 – 1:	Cfl- s1 (alt B1)														

Ecological characteristics

DIBt-AgBB Schema	AbZ.: Z-156.601-878
Conformity certificate	1658-CPD-1210
PRODIS / GUT - ID	Lizenz-Nr.: B29F001B
EPD (Environmental Product Declaration)	EPD-GUT-2009311-D

Fastness

Light fastness	≥ 5
Water fastness	≥ 4
Friction fastness	≥ 3-4

01/2012 Subject to production technical changes

