

OBJECT CARPET

Typical characteristics EN 1307

Name of article:
Method of production ISO 2424:
Width ISO 3018:
Surface structure ISO 2424:
Colourways ISO 2424:
Pile material:
Primary backing ISO 2424:
Secondary backing ISO 2424:
Overall weight ISO 8543:
Overall thickness ISO 1765:
Mass of effective pile ISO 8543:
Pile service weight:
Effective pile thickness ISO 1766:
Pile density ISO 8543:
Stitch rate ISO 1763:

Web Art Pebble Beach 600

woven
ca. 190 cm
cut
patterned Rapport/pattern repeat L 52 cm x B 95,0 cm
100% Polyamid Antron®
synthetisch / synthetic / synthétique
Appretur
ca. 1.500 g/m²
ca. 4,5 mm
ca. 470 g/m²
ca. 650 g/m²
ca. 3,1 mm
ca. 0,122 g/cm³
ca. 115.000/m²

Application

Wearability: 32
Comfort class: LC 1

Physical features as to the building

Electrostatic loading: < 2 KV
Surface resistivity: 10⁹Ω
Sound absorption: +18 dB
Acoustical absorption α_w: 0.15
Sound absorption α_s:

Hz	125	250	500	1000	2000	4000
α _s	0,01	0,01	0,03	0,14	0,23	0,11

Transparency to heat: ca. 0,06 K*m²/W
Flammability EN 13 501 – 1: Cfl- s1 (alt B1)

Ecological characteristics

DIBt-AgBB Schema AbZ.: Z-156.601-879
Conformity certificate 1658-CPD-1210
PRODIS / GUT - ID Lizenz-Nr.: 058533B7
EPD (Environmental Product Declaration) EPD-GUT-20091111-D

Fastness

Light fastness ≥ 5
Water fastness ≥ 4
Friction fastness ≥ 3-4

01/2012 Subject to production technical changes

