


# OBJECT CARPET

## Typical characteristics

|                               |  |
|-------------------------------|--|
| Name of article               |  <b>Allure 1000</b> |
| Method of production ISO 2424 | tufted   |
| Width ISO 3018                | approx. 400 cm   |
| Surface structure ISO 2424    | Loop   |
| Colourways ISO 2424           | Mix  |
| Pile material ISO 2424        | 100% Econyl® by Aquafil  |
| Primary backing ISO 2424      | PES  |
| Secondary backing ISO 2424    | Conductive action back   |
| Overall weight ISO 8543       | approx. 2300 g/m <sup>2</sup>  |
| Overall thickness ISO 1765    | approx. 7,0 mm   |
| Pile service weight           | approx. 1000 g/m <sup>2</sup>  |
| Additional equipment          | OC Protect   |

## Application

|                       |                           |
|-----------------------|---------------------------|
| Wearability EN 1307   | commercial use heavy (33) |
| Comfort class EN 1307 | LC4                       |

## Ecological characteristics

|   |                          |
|---|--------------------------|
| Conformity certificate                  | 1658-CPR-3032            |
| DOP                                     | 1045-124859              |
| EPD (Environmental Product Declaration) | EPD-GUT-20160117-CCA1-EN |

## Fastness

|                                  |       |
|----------------------------------|-------|
| Light fastness ISO 105-B02       | ≥ 5   |
| Water fastness EN ISO 105 E01    | ≥ 4   |
| Friction fastness EN ISO 105-X12 | ≥ 3-4 |



Daten Stand 30.11.2017. Durch technische Weiterentwicklung bedingte Veränderungen vorbehalten.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf  
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com