

# ASPECTA TEN TENDER RECOMMENDATIONS



**ASPECTA**  
TEN

Featuring  ISOCORE Technology®

Quantity	Product description			Total price
	Flooring type	EN 16511	Semi-rigid multilayer modular floor covering (MMF)	
	Classification	EN ISO 10874	34	
	Wear layer thickness	EN ISO 24340 / EN 429	0.7mm	
	Top layer	LVT	3.0mm	
	Extruded vinyl core	ISOCORE Technology®	5.0mm	
	Pre-attached underlayment	IXPE with Ultra-Fresh	2.0mm	
	Gauge	ISO 24337	10.0mm	
	Total weight	EN ISO 23997 / EN 430	10.8kg/m <sup>2</sup>	
	Fire behaviour	EN 13501-1	Bfl-s1	
	Slip resistance	EN 13893	DS	
	Slip resistance	DIN 51130	Results vary by emboss	
	Brindle Oak, Corneto, Fulton Hyde, Runyon Oak, Tally Oak, Tanley Hall, Urban Grid		R10	
	Crescent Oak		R9	
	Factory surface treatment	CERAMIC BEAD Urethane coating with Ceramic Bead particles		
	Plasticizer	DOTP phthalate-free		
	Limited Commercial Warranty	25 years material		
	Impact sound insulation	EN ISO 10140-3 ISO 717-2 EN ISO 140-8	18dB	
	<b>WOODS</b>			
	BRINDLE OAK - Size 220mm x 1510mm - Emboss IN-REGISTER - Bevelled edge			
	CRESCENT OAK - Size 219mm x 1819mm - Emboss IN-REGISTER - Bevelled edge			
	RUNYON OAK - Size 220mm x 1510mm - Emboss IN-REGISTER - Bevelled edge			
	TALLY OAK - Size 220mm x 1510mm - Emboss IN-REGISTER - Bevelled edge			
	TANLEY HALL - Size 220mm x 1510mm - Emboss IN-REGISTER - Bevelled edge			
	<b>STONE, MASONRY &amp; LEATHER</b>			
	CORNETO - Size 448mm x 906mm - Emboss CORAL - Bevelled edge			
	FULTON HYDE - Size 448mm x 906mm - Emboss CALF SKIN - Bevelled edge			
	URBAN GRID - Size 448mm x 906mm - Emboss HONED STONE - Bevelled edge			
	Article number and description			
m <sup>2</sup>	Price per sqm			€