



Chroma Office Solid

PRODUCT SPECIFICATION

Product Dimension	500mm x 500mm Tile
Product Construction	Loop Pile Tufted
Pile Composition	100% Aquafil Alto Chroma SD BCF Nylon 700 dtex
Total Mass/Unit Area	4375g/m ² nominal
Pile Mass/Unit Area	575g/m ² + / - 7.5%
Stitch Rate	39st/100mm
Tufts per m²	153,500
Gauge	1/10"
Backing	PMB (polymer modified bitumen), Cushion Backing available on request
Total Thickness	6.1mm
Pile Height	3mm
Tiles per Box	20 Tiles = 5m ²
Colours	12

Chroma reserves the right to change or modify specifications.

PERFORMANCE

	Heavy Contract
Wear Rating	(10 year guarantee)

TECHNICAL PROPERTIES

Castor Chair Test BS EN 985:1995	Suitable for continuous use
Static Electricity BS EN 1815:1998	Stroll Test = < 2 Kv body volts
Acoustic Impact Noise Reduction	Bitumen = 21dB

Flammability:	Euroclass	Bfl-S1
Dimensional Stability		<0.2%
Fastness BS EN ISO 105	Light:	>5
	Water:	5
	Wet/Dry:	5
	Shampoo:	5