


OBJECT CARPET

Typical characteristics

Name of article	 Silky Seal 1200
Method of production ISO 2424	Tufted
Width ISO 3018	approx. 400 cm
Surface structure ISO 2424	Cut
Colourways	Uni
Pile material ISO 2424	100% PA 6.6 Antron®
Primary backing ISO 2424	PES
Secondary backing ISO 2424	BlackThermo®Filz Acoustic Plus
Overall weight ISO 8543	approx. 2700 g/m ²
Overall thickness ISO 1765	approx. 11,0 mm
Pile service weight	approx. 1200 g/m ²

Application

Wearability EN 1307	commercial use general (32)
Comfort class EN 1307	LC4

Ecological characteristics

Conformity certificate	CE - System 3
DOP	1045-118356
EPD (Environmental Product Declaration)	EPD-GUT-20160118-CCA1-EN

Fastness

Light fastness ISO 105-B02	≥ 5
Water fastness EN ISO 105 E01	≥ 4
Friction fastness EN ISO 105-X12	≥ 3-4



Release Date 14.5.2018.

OBJECT CARPET GmbH Rechbergstrasse 19 D-73770 Denkendorf
Fon +49 (0) 711 / 34 02-0 Fax +49 (0) 711 / 34 02-122 technicalsupport@object-carpet.com